

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-29 (Cancelled)

30. (Currently Amended) A method of communicating, [[said]] the method comprising:
maintaining a connection, via a network, between a first proxy on a first server and a
second proxy on a second server;
while maintaining the connection:
a plurality of first processes on the first server communicating with a plurality
of second processes on the second server via the connection by:
the plurality of first processes exchanging data with the first
proxy via shared memory, wherein each of the plurality
of first processes is assigned a unique region of the
shared memory, and
wherein exchanging data with the first proxy includes, for each
first process of the plurality of first processes:
the each first process writing data to the respective
unique region assigned to the each first process,
and the first proxy reading data from the
respective unique region assigned to the each
first process; and
the first proxy writing data to the respective unique
region assigned to the each first process, and the
each first process reading data from the

respective unique region assigned to the each

first process; and

[[said]] the first proxy transmitting exchanging the [[said]] data
via [[said]] the connection to said with the second
proxy.

31. (Currently Amended) The method of Claim 30, wherein the plurality of first processes exchanging data with the first proxy via shared memory comprises:

a first process of the plurality of first processes writing data to a region of the shared memory that is assigned to the first process; and

the first process causing the state of a process mark device to change to a first state to indicate that the region is not writeable by the first process, wherein the process mark device has the first state and a second state that indicates that the region is writeable by the first process.

32. (Currently Amended) The method of Claim 31, wherein the plurality of first processes exchanging data with the first proxy via shared memory further comprises:

prior to the first process writing data to the region of the shared memory that is assigned to the first process, the first process determining whether the region of the shared memory is currently writeable by the first process.

33. (Currently Amended) The method of Claim 32, wherein the first process determining whether the region of the shared memory that is assigned to the first process is currently writeable comprises the first process checking the state of the process mark device.

34. (Currently Amended) The method of Claim 33, further comprising the first process causing the state of a proxy mark device to change to a first state to indicate that the region of the shared memory that is assigned to the first process is readable by the first proxy, wherein the proxy mark device has the first state and a second state that indicates that the region that is assigned to the first process is not readable by the first proxy.

35. (Previously Presented) The method of Claim 34, wherein the first process causing the state of the proxy mark device to change to the first state comprises the first process writing to the process mark device.

36. (Currently Amended) The method of Claim 34, wherein the plurality of first processes exchanging data with the first proxy via shared memory further comprises:
in response to the proxy mark device changing to the first state, the first proxy
determining that there is data to be read from the region of the shared memory that is assigned to the first process.

37. (Currently Amended) The method of Claim 34, wherein the plurality of first processes exchanging data with the first proxy via shared memory further comprises:
the first proxy reading data from the region of the shared memory that is assigned to the first process; and
the first proxy causing the proxy mark device to change to the second state.

38. (Previously Presented) The method of Claim 37, further comprising:
the process mark device changing to the second state in response to the proxy mark device changing to the second state.

39. (Currently Amended) The method of Claim 30, wherein the plurality of first processes exchanging data with the first proxy via shared memory comprises:

- a first process of the plurality of first processes reading data from a region of the shared memory that is assigned to the first process; and
- the first process causing the state of a process mark device to change to a first state to indicate that the region of the shared memory that is assigned to the first process is not readable by the first process, wherein the process mark device has the first state and a second state that indicates that the region of the shared memory that is assigned to the first process is readable by the first process.

40. (Currently Amended) A communication system, comprising:

- a first server comprising:
 - a plurality of first processes;
 - a first proxy; and
 - a first shared memory having a plurality of slots to store first data to be exchanged between the first processes and the first proxy; each slot being assigned to a particular one of the first processes;
 - a second server comprising:
 - a plurality of second processes;
 - a second proxy; and
 - a second shared memory having a plurality of slots to store second data to be exchanged between the second processes and the second proxy; each slot being assigned to a particular one of the second processes;
- wherein the first proxy is configured to maintain a connection, via a network, with the second proxy; [[and]]

wherein the first proxy and the second proxy are configured to exchange the first data and the second data via the connection to allow the plurality of first processes to communicate with the plurality of second processes; and

wherein the first proxy and the plurality of first processes exchange data by, for each first process of the plurality of first processes:

each first process writing data to a respective slot assigned to the each first process, and the first proxy reading data from the respective slot assigned to the each first process; and

the first proxy writing data to the respective slot assigned to the each first process, and the each first process reading data from the respective slot assigned to the each first process.

41. (Previously Presented) The communication system of Claim 40,
wherein the first server further comprises:

a plurality of process mark devices, at least one mark device being
assigned to each slot to regulate data flow into and out of the
slots of the shared memory, and
a plurality of proxy mark devices, each mark device corresponding to
one of the process mark devices,
wherein each process mark device is configured to cooperate with the
corresponding proxy mark device to regulate data being
inputted to and outputted from the corresponding slot.

42. (Currently Amended) A computer readable medium having stored thereon
instructions, which when executed on one or more processors, cause the one or more
processors to perform the steps of:

maintaining a connection, via a network, between a first proxy on a first server
and a second proxy on a second server;

while maintaining the connection:

a plurality of first processes on the first server communicating with a
corresponding plurality of second processes on the second
server via the connection by:

the plurality of first processes exchanging data with the first
proxy via shared memory, wherein each of the plurality
of first processes is assigned a unique region of the
shared memory, and

wherein exchanging data with the first proxy includes, for each

first process of the plurality of first processes:

the each first process writing data to the respective

unique region assigned to the each first process,

and the first proxy reading data from the

respective unique region assigned to the each

first process; and

the first proxy writing data to the respective unique

region assigned to the each first process, and the

each first process reading data from the

respective unique region assigned to the each

first process; and

[[said]] the first proxy ~~transmitting~~ exchanging the

[[said]] data via [[said]] the connection ~~to said~~

with the second proxy.

43. (Currently Amended) The computer readable medium of Claim 42, wherein the step of the plurality of first processes exchanging data with the first proxy via shared memory comprises:

a first process of the plurality of first processes writing data to a region of the shared memory that is assigned to the first process; and
the first process causing the state of a process mark device to change to a first state to indicate that the region is not writeable by the first process, wherein the process mark device has the first state and a second state that indicates that the region is writeable by the first process.

44. (Currently Amended) The computer readable medium of Claim 43, wherein the step of the plurality of first processes exchanging data with the first proxy via shared memory further comprises:

prior to the first process writing data to the region of the shared memory that is assigned to the first process, the first process determining whether the region of the shared memory is currently writeable by the first process.

45. (Currently Amended) The computer readable medium of Claim 44, wherein the step of the first process determining whether the region of the shared memory that is assigned to the first process is currently writeable comprises the first process checking the state of the process mark device.

46. (Currently Amended) The computer readable medium of Claim 45, wherein the method further comprises the step of the first process causing the state of a proxy mark device to change to a first state to indicate that the region of the shared memory that is assigned to the first process is readable by the first proxy, wherein the proxy mark device has

the first state and a second state that indicates that the region of the shared memory that is assigned to the first process is not readable by the first proxy.

47. (Previously Presented) The computer readable medium of Claim 46, wherein the step of the first process causing the state of the proxy mark device to change to the first state comprises the first process writing to the process mark device.

48. (Currently Amended) The computer readable medium of Claim 46, wherein the step of the plurality of first processes exchanging data with the first proxy via shared memory further comprises:

in response to the proxy mark device changing to the first state, the first proxy
determining that there is data to be read from the region of the shared memory that is assigned to the first process.

49. (Currently Amended) The computer readable medium of Claim 46, wherein the step of the plurality of first processes exchanging data with the first proxy via shared memory further comprises:

the first proxy reading data from the region of the shared memory that is assigned to the first process; and
the first proxy causing the proxy mark device to change to the second state.

50. (Previously Presented) The computer readable medium of Claim 49, wherein the method further comprises the step of:

the process mark device changing to the second state in response to the proxy mark device changing to the second state.

51. (Currently Amended) The computer readable medium of Claim 42, wherein the step of the plurality of first processes exchanging data with the first proxy via shared memory comprises:

a first process of the plurality of first processes reading data from a region of the shared memory that is assigned to the first process of the shared memory that is assigned to the first process; and

the first process causing the state of a process mark device to change to a first state to indicate that the region is not readable by the first process, wherein the process mark device has the first state and a second state that indicates that the region of the shared memory that is assigned to the first process is readable by the first process.